

Title: Review of water quality models simulating in-stream nutrient dynamics (Abstract ID: 747129)

Authors: Sushant Mehan¹, Margaret Kalcic¹, Jim Hood²

¹Department of Food, Agricultural, and Biological Engineering, ²Department of Evolution, Ecology, and Organismal Biology, The Ohio State University, Columbus, Ohio, U.S.A.

Abstract

Many waterbodies around the world are adversely impacted by harmful algal blooms (HABs). One primary driver of these blooms is often high concentrations of anthropogenic phosphorus loading. The phosphorus mitigation plans require accurate information on nutrient sources and transport, to and through water bodies, including the stream network. Diffuse sources, are particularly difficult to quantify due to the cost of in situ monitoring, and is often supplemented using various water quality models. SWAT, a comprehensive watershed-scale model, is widely used to assess and improve downstream water quality using QUAL2E equations. EPA developed QUAL2E can model phytoplankton growth but has a limited capacity to model benthic algae. Although SWAT requires a lesser number of parameters while simulating water quality outputs, unlike, HSPF, INCA, SPARROW, WASP, and MIKE-SHE, the water quality algorithm within SWAT needs modifications for simulating phosphorus legacy within the waterbodies. This study reviews the existing water quality models to improve the water quality algorithm within SWAT. Most of the water quality models can simulate processes, including the proliferation of fixed and floating algal biomass and phosphorus cycling (QUAL2E/K, WASP, HSPF). Some water quality models are better in simulating the time dependent factors, such as light attenuation, form and concentration of nutrients, and water temperature (HSPF, INCA). There are a few water quality algorithms that can simulate both horizontal stream flow and shallow flow (SHETRAN, INCA). Both horizontal and shallow flow takes into account the anisotropy and variable biogeochemistry impacts on the turbulence of water, thus, the water quality. Some water quality models simulate the non-linear relationship between nutrient concentration and discharge timing and magnitude (SPARROW). There are some commercialized models like MIKE-SHE that simulate reasonably good results, but the water quality algorithm/equation/process is not publically available. Our review of the existing water quality models will help in identifying, modifying, and implementing the SWAT source code revisions required to improve and mitigate water quality degradation from a finer spatial scale, including small ditches and streams, to the large-scaled watershed over time.

Keywords: Water-Quality Models; Soil and Water Assessment Tool; In-Stream Processes; Nutrient Dynamics; Harmful Algal Blooms (HABs)

BACKGROUND

1. Eutrophication, which is commonly caused by elevated levels of reactive forms of phosphorus (P), increases the prevalence of harmful algal blooms and hypoxia while decreasing water quality (Conley, 2000; Mainstone et al., 2000; Bennett et al., 2001).
2. Sources of reactive P include point sources (e.g., discharges from industrial and municipal wastewater) and non-point sources (e.g., agricultural runoff, septic tank leaks, and riverbank erosion). Often, non-point sources are difficult or prohibitively expensive to quantify (Jarvie et al., (2002, 2005)). Process-based models offer a low cost and flexible approach for estimating the magnitude and impact of difficult to quantify non-point sources.
3. To model nutrient cycling within a process-based water quality model, modelers often make several assumptions. Some models often ignore high-resolution spatial variability (small streams, ditches). Simultaneously, others simplify the different processes controlling P cycling within the rivers/streams (Withers and Jarvie, 2008). Here, we focus on the implications of ignoring or naively modeling instream P cycling.
4. In-stream P cycling processes (e.g., uptake/release, adsorption/desorption, coprecipitation/dissolution, and advection/diffusion) can have substantial impacts on the magnitude, timing, and form of P exports to recipient ecosystems (Vannote et al., 1980; Bryce et al., 1999; Allan, 2004). For example, Jarvie et al. (2011) showed that the Sandusky and Thames Rivers retained up to 48% and 14% of P flux on an annual scale. Thus, accounting for instream processes in the water quality model is essential for characterizing the impact of non-point P sources on P exports to recipient ecosystems.
5. Some commercialized models can simulate reasonably the different in-stream processes, but the water quality algorithm/equation/process is not publicly available. On the other hand, an open-source, distributed, and process-based hydrologic and water quality model, namely, the Soil and Water Assessment Tool (SWAT), has been explicitly used in the science community last 30 years (Arnold et al., 1998).
6. This study aims to identify the limitations within the SWAT model in simulating various in-stream processes.

IN-STREAM PHOSPHORUS CYCLING

In-stream phosphorus cycling includes redistribution pathways where the transformation of P from inorganic to organic and back to dissolved form takes place (Figure 1).




Figure 1. Phosphorus cycling with mass transfer and model kinetics

where, R_{pa} is the amount of Phosphorus within per unit biomass of phytoplankton (1mg P / 1.25 mg Phytoplankton Biomass algae) (Filstrup and John, 2017); p_o is organic phosphorus; p_i is inorganic phosphorus; IP is the sum of phytoplankton phosphorus and benthic algae phosphorus; h hydrolysis; u is uptake by aquatic biota; e is the excretion from sediments and aquatic biota detritus; s is settling, and se is the sediment exchange.

Redistribution pathways include different processes. Erosion of stream channels during high flow conditions, remobilization of P due to physical disturbance of bed sediments or macrophyte communities, the release of P from bed sediments, or death of aquatic biota (Figure 2).




Figure 2. Conceptual diagram of in-stream processes influencing P concentration in flowing waters. (Adapted from Withers and Jarvie, 2008)

SWAT In-Stream Processes (Developments and Limitations)

In SWAT, the concentration of algae in the stream drives P nutrient cycling

The growth of algae is decided by the rate at which “chlorophyll a” grows or decays, the respiration rate of phytoplanktons, settling rate, and amount of algae present in the stream

$$\Delta \text{algae} = \left((\mu_a \cdot \text{algae}) - (\rho_a \cdot \text{algae}) - \left(\frac{\sigma_1}{\text{depth}} \cdot \text{algae} \right) \right) \cdot TT$$

Δalgae = change in algal biomass concentration, mg alg/L

μ_a = local specific growth rate of algae, day⁻¹ or h⁻¹

ρ_a = local respiration or death rate of algae, day⁻¹ or h⁻¹

σ_1 = local settling rate for algae, $\frac{m}{day}$ or $\frac{m}{hr}$

depth = depth of water in the channel, m

algae

= algal biomass concentration at the beginning of the day, mg – alg/L

TT = Flow travel time in the reach segment (day or h)

However, SWAT ignores organic forms of phosphorus are generated by algae's death

Also, it was observed that SWAT in-stream kinetics formulation does not apply to any species other than phytoplankton

To overcome the limitation Santhi et al., 2001, introduced a first-order decay kinetic function that included periphyton. The function was developed to characterize the microbial transformation of in-stream soluble P to organic P with respect to flow conditions.

$$PC_o = PC_i \times e^{-a(\frac{chl}{q})}$$

$$\Delta SP = SP_i - SP_o$$

$$OP_o = OP_i + \Delta SP$$

PC_o and PC_i are reach soluble P inflow and outflow concentrations in $\frac{g}{m^3}$

“a” is the degradation coefficient

“chl” is channel length in km

“q” is flow rate in mm/day;

SP_i and SP_o are the inflow and outflow soluble P loads in kg

OP_i and OP_o are the inflow and outflow organic P loads in kg

On the contrary, White et al. 2014 observed that the existing in-stream P submodel within SWAT does not adequately represent the in-stream processes associated with suspended algae systems, specific to the site, Illinois River Watershed in Oklahoma.

The SWAT water quality sub-routine (QUAL2E) was replaced with the routine that represents streambed storage and SRP interactions within the water column.

Although, the modified SWAT in-stream routine has performed well in many regions but may not be equally applicable to all areas.

(A) Soluble Phosphorus In-stream Submodel

$$EPC = \frac{\sum_{t=1}^{-DI} SP_t \left(1 + \frac{t}{DI}\right)}{\sum_{t=1}^{-DI} \left(1 + \frac{t}{DI}\right)}$$

$$EPC > SP_{in}$$

$$SP_{out} = EPC + (SP_{in} - EPC)e^{-K_{out} TT}$$

$$EPC < SP_{in}$$

$$SP_{out} = EPC + (SP_{in} - EPC)e^{-K_{in} TT}$$

$$SP_{trans} = SP_{in} + (1 - e^{-SPTT} EPC)$$

EPC = Equilibrium Phosphorus Concentration
SP_t = soluble phosphorus concentration on day "t" in mgL^{-1}
DI = period of influence in days (user specified)
SP_{in} and *SP_{out}*
= Concentrations of Soluble P entering and leaving the reach in mgL^{-1}
K_{in} and *K_{out}* =
soluble P transformation coefficients into and out of the benthic sediments
TT = Travel time in reach in hours

(B) Particulate Phosphorus In-stream Submodel

$$f_{bf} = \frac{Q}{Q_{bf}}$$

$$PP_{out} = PP - PP \frac{(F_{bf} - F_{dep})}{(F_{eqv} - F_{dep})}$$

$$PP_{out} = PP - BP_{conc} \frac{(F_{bf} - F_{eqv})}{(F_{eqv} - F_{eq})}$$

f_{dep} = bank flow condition where 100 % deposition takes place
f_{scr}
= bank flow condition where 100 % scouring from streambed
f_{eqv}
= bankflow condition where deposition is equivalent to scouring
PP = Particulate P concentration in the reach water column
PP_{out} = Particulate P concentration leaving the reach
BP_{conc} = Concentration of benthic P in the water column if 100% of
benthic P were released

Proposed SWAT In-stream Water Quality Processes Modifications

The review of different in-stream algorithms within SWAT to date proves that there is a scope of improvement in the water quality algorithm to include both suspended and benthic P forms.

A simplified in-stream P cycle is shown in Figure 3.




Figure 3. A proposed modified in-stream P cycle

Conclusions & References

The limitations of the existing water quality algorithm with SWAT can direct modifications within SWAT source code to enhance the ability of SWAT to simulate in-stream processes.

The modified revision of SWAT for simulating in-stream water quality will be tested at local and regional scales to test its efficacy.

REFERENCES

1. Allan, J.D. (2004). Landscapes and riverscapes: the influence of land use on stream ecosystems. *Ann Rev Ecol Evolut Syst* 35:257–84.
2. Arnold, Jeffrey G., Raghavan Srinivasan, Ranjan S. Muttiah, and Jimmy R. Williams. "Large-area hydrologic modeling and assessment part I: model development 1." *JAWRA Journal of the American Water Resources Association* 34, no. 1 (1998): 73-89.
3. Bennett, E.M., Carpenter, S.R. and Caraco, N.F. (2001). Human impact on erodible phosphorus and eutrophication: a global perspective. *Bioscience* 51 (3), 227-234.
4. Bryce S.A., Omernik J.M., Larsen D.P. (1999). Ecoregions: a geographic framework to guide risk and ecosystem management. *Environ Pract*,1:141–55
5. Conley, D.J. (2000). Biogeochemical nutrient cycles and nutrient management strategies. *Hydrobiologia* 410, 87-96.

6. Filstrup, Christopher T., and John A. Downing. (2017) "Relationship of chlorophyll to phosphorus and nitrogen in nutrient-rich lakes." *Inland Waters* 7(4): 385-400.
7. Jarvie, H.P., Neal, C., Withers, P.J., Baker, D.B., Richards, R.P., and Sharpley, A.N. (2011). Quantifying phosphorus retention and release in rivers and watersheds using extended end-member mixing analysis (E-EMMA). *Journal of Environmental Quality*, 40(2), pp.492-504.
8. Jarvie H.P., Jurgens M.D., Williams R.J., Neal C., Davies J.J.L., Barrett C., et al. (2005) Role of river bed sediments as sources and sinks of phosphorus across two major eutrophic UK river basins: the Hampshire Avon and Herefordshire. *J Hydrol*;304:51–74.
9. Jarvie H.P., Neal C., Williams R.J., Sutton E.J., Neal M., Wickham H.D., et al. (2002) Phosphorus sources, speciation and dynamics in the lowland eutrophic River Kennet, UK. *Sci Tot Environ*;282–283:175–203.
10. Mainstone, C.P., Parr, W., and Day, M. (2000). *Phosphorus and River Ecology: Tackling Sewage Inputs*. English Nature (now Natural England), Peterborough, UK. 46 pp.
11. Santhi, C., Jeffrey G. Arnold, Jimmy R. Williams, William A. Dugas, Raghavan Srinivasan, and Larry M. Hauck. (2001) "Validation of the swat model on a large river basin with point and nonpoint sources 1." *JAWRA Journal of the American Water Resources Association* 37 (5): 1169-1188.
12. Vannote R.L., Minshall G.W., Cummins K.W., Sedell J.R., Cushing C.E. (1980). The river continuum concept. *Can J Fish Aqu Sci* 37:130–7.
13. White, Michael J., Daniel E. Storm, Aaron Mittelstet, Philip R. Busteed, Brian E. Haggard, and Colleen Rossi. (2014). Development and testing of an in-stream phosphorus cycling model for the Soil and Water Assessment Tool." *Journal of environmental quality* 43 (1): 215-223.
14. Withers, P.J.A., and Jarvie, H.P. (2008). Delivery and cycling of phosphorus in rivers: a review. *Science of the total Environment*, 400(1-3), pp.379-395.