

Validity of analytical solutions for the groundwater response to Earth tides

Jose M. Bastias Espejo ¹, Gabriel C. Rau ^{1,2}, Philipp Blum ¹

¹Institute of Applied Geosciences (AGW), Karlsruhe Institute of Technology (KIT), Karlsruhe, Germany

²School of Environmental and Life Sciences, The University of Newcastle, Newcastle, Australia

Key Points:

- We develop and verify an advanced simulator for the well water level response to Earth tides
- Subsurface property estimation requires undrained and confined conditions occurring at depths > 50 m
- Amplitudes and phases from numerical and analytical solutions systematically diverge reflecting theory simplifications

Corresponding author: Jose M. Bastias Espejo, jose.bastias@kit.edu

Abstract

Harmonic Earth tide components in well water levels have been used to estimate hydraulic and geomechanical subsurface properties. However, the validity of various methods based on analytical solutions has not been established. First, we review the theory and examine the latest analytical solution used to relate well water levels to Earth tides. Second, we develop and verify a novel numerical model coupling hydraulics and geomechanics to Earth tide strains. Third, we assess subsurface conditions over depth for a range of realistic properties. Fourth, we simulate the well water level response to Earth tide strains within a 2D poroelastic layered aquifer system confined by a 100 m thick aquitard. We find that the analytical solution matches two observations (amplitudes and phases) to multiple unknown parameters leading to non-unique results. We reveal that undrained and confined conditions are necessary for the validity of the analytical solution. This occurs for the dominant M_2 frequency at depths > 50 m and requires specific storage at constant strain of $S_\epsilon \geq 10^{-6}$, hydraulic conductivity of the aquitard of $k_l \leq 5 \cdot 10^{-5} \text{ ms}^{-1}$ and aquifer of $k_a \geq 10^{-4} \text{ ms}^{-1}$. We further illustrate that the analytical solution is valid in unconsolidated systems, whereas consolidated systems require additional consideration of the Biot modulus. Overall, a priori knowledge of the subsurface system supports interpretation of the groundwater response. Our results improve understanding of the effect of Earth tides on groundwater systems and its interpretation for subsurface properties.

Plain Language Summary

Earth tide induced strains in the subsurface lead to well water level fluctuations in groundwater monitoring wells. This groundwater response has been interpreted with analytical solutions to estimate aquifer properties. However, analytical solutions are based on simplified assumptions whose conditions of validity have not yet been tested. We develop a new approach to simulate the influence of Earth tides on groundwater based on fundamental physical principles. We simulate realistic conditions and compare our results to those from analytical solution to determine the hydraulic and subsurface conditions under which simplified interpretations are valid. Our results improve understanding of the effects of Earth tides on groundwater systems and interpretation of subsurface properties from well water levels.

1 Introduction

Earth tides have long been observed to influence groundwater systems (Meinzer, 1939), a phenomenon that is commonly expressed as harmonic water level fluctuations in monitoring wells (Merritt, 2004). Analytical solutions based on simplified concepts have been developed to enable calculation of subsurface hydraulic and geomechanical properties (Cuttillo & Bredehoeft, 2011; Wang & Manga, 2021; Rau, Cuthbert, Acworth, & Blum, 2020). Since Earth tides are a ubiquitous natural force, their response should be contained in the data from numerous wells around the world. In fact, a recent review found that interpreting the groundwater response to Earth tides is underutilized and that further development offers the potential for widespread application, which in turn would lead to increased knowledge of the subsurface (McMillan et al., 2019).

Estimating subsurface hydro-geomechanical properties requires good quality monitoring data of groundwater and Earth tides (Merritt, 2004; Rau, Cuthbert, Post, et al., 2020). Of main interest are the amplitude ratio and phase shift between the Earth tide strain and its well water level response. The first step is to extract the subtle harmonic components whose frequencies are well defined (Rojstaczer, 1988; Rojstaczer & Riley, 1990). Various approaches have been used to identify and extract the dominant amplitudes and phases (Turnadge et al., 2019). Recent research illustrated that least-squares

fitting of the dominant harmonic tidal components to measurements provides the most robust results (Schweizer et al., 2021).

Early research developed and tested an analytical solution to estimate subsurface properties from the relationship between strain and water levels in a fully confined aquifer (Cooper Jr et al., 1967; Hsieh et al., 1987). This was extended to include leaky conditions and allow concurrent use of multiple frequencies (Rojstaczer, 1988; Rojstaczer & Riley, 1990). Rojstaczer and Agnew (1989) studied the dependency of porosity and elastic parameters to a real deformation of a poro elastic medium. High sensitivity was reported when the applied strains occurs in low porosity and the increase with decreasing compressibility (inverse of the bulk modulus) of the solid matrix.

Field measurements of the groundwater response to Earth tides has resulted in negative and positive phase shifts between strain and well water levels. Negative phase shifts are interpreted as fully confined conditions and horizontal flow only (Hsieh et al., 1987). For example, hydraulic conductivity and specific storage were estimated from negative phase shifts (Xue et al., 2016; Allègre et al., 2016). However, positive phase shifts in the field were also observed and attributed to vertical flow through leaky aquitards (Roeloffs et al., 1989). This was interpreted using the analytical solution of vertical flow in an homogeneous aquifer caused by a harmonic load or stress (Wang, 2017).

Recent research included modifications to the original analytical solution by Hsieh et al. (1987) to account for more realistic conditions. Most notable is the work by Wang et al. (2018) who developed an extended analytical solution which includes vertical leakage to model a two-layered aquifer system. Gao et al. (2020) investigated the well skin effect which originates from the fact that the formation around a well is disturbed and well water storage on the well water level response to Earth tides. The authors found that the skin effect may significantly delay the well water level phase response to Earth tides. In addition, Guo et al. (2021) developed a model for tidal response with a fault passing through the aquifer based on a fault-guided fracture network to estimate fracture properties. They found that the hydraulic diffusivity in the fault damage zone higher than previously established values, but also that it remains below estimates based on induced seismicity migration. Sun et al. (2020) reviewed four of the most common analytical models to estimate hydraulic properties with Earth tidal analysis. They estimated hydraulic properties from a real data set and provide a range of applicability of the different models based on the transmissivity of the aquifer.

While analytical models offer a convenient approach to estimate hydraulic properties, their applicability is limited through simplifying assumptions arising from fundamental physics, conceptual model or boundary conditions. These include for example only radial flow, negligible horizontal displacement of the aquifer, confined conditions and undrained conditions, unconsolidated materials and no gravity. But it has been reported that some of these assumptions may significantly influence the estimated subsurface properties (Wang et al., 2019; Zhu & Wang, 2020).

Numerical modeling of tidal effects is common in coastal (Abarca et al., 2013; Zhang et al., 2021) and adjacent settings (Jardani et al., 2012; Pendiuk et al., 2020; Alcaraz et al., 2021), likely because the loading effect of ocean tides is much larger than that caused solely by Earth tide forces. So far, modeling the subsurface response to ocean tides has considered poro elastic conditions and harmonic loading by the weight of the water, therefore, solved as a consolidation problem. In contrast, the pressurization of an inland aquifer is produced by changes in the pore space volume of the porous material due to strains (i.e., eigenstrains) caused by the gravitational influence from the movement of celestial bodies. Moreover, the change of the confined pore pressure is generally measured using an observation well which causes fluid movement.

To the best of our knowledge, only hydraulic modeling approaches neglecting any geomechanical effects, i.e., groundwater flow without coupled poro elasticity, have so far been used to investigate the groundwater response to Earth tides. For example, Wang et al. (2019) simulated the effect of capillarity of the unsaturated zone in one dimension. They found out that the assumption of fixed water table can lead to erroneous estimation of subsurface properties. Zhu and Wang (2020) simulated a two layered system to study the effect of leakage through an aquitard and concluded that simplifications in the analytical model lead to overly conservative estimates of vertical flux between layers. Wang and Manga (2021) provide a summary of these works.

The confined pore pressure generated as result of Earth tide strains is a mechanical phenomenon caused by the elastic deformation of the porous matrix. Furthermore, unlike for traditional hydraulic testing approaches, there is a general lack of work investigating the effect of realistic conditions and assumptions on interpretations using analytical solutions. Investigating the influence of limiting assumptions and realistic subsurface conditions to better understand the applicability of analytical solutions requires development of more advance numerical models that also consider coupling with geomechanics.

The objective of this study is therefore to (1) develop a numerical model for the groundwater responses to Earth tides, which couples hydraulic and geomechanical processes, (2) critically examine assumptions upon which analytical solutions are based, (3) investigate and compare response conditions as well as the influence of geomechanical properties. Thus, our work significantly improves our understanding of the coupled physics, which controls the well response in a poro elastic medium. These results can act as a practical guide for improved estimation of aquifer properties due to the groundwater response to Earth tides.

2 Methodology

2.1 Fundamental theory of the groundwater response to Earth tides

Earth tides are displacements of the solid Earth's crust caused by the gravitational forces of celestial bodies that move in relation to the Earth. Such displacements are typically expressed as harmonic signals that can be predicted from well-known astronomical relationships. Earth tide forces are dominant at distinct frequencies within the semi-diurnal and diurnal range, e.g., M_2 at 1.97322 cycles per day (cpd) or S_1 at 1.0 cpd. Under tidal forcing, the pore volume of the subsurface elastically deforms depending on the mechanical properties of the filling material resulting in a small change of volume. If the subsurface is saturated, the filling fluid has to adapt to the new available pore space which raises or lowers the pore pressure. The processes can be mathematically represented by the *Biot* consolidation theory.

Biot (1941) developed the constitutive laws which relate the applied forces (stresses) with deformation (strains) and motion within a compressible porous medium. For the purpose of modeling, these laws are formulated in the form of mathematical equations which consist of four basic variables stress (σ_{ij}), strain (ϵ_{ij}), pore pressure (p_f) and incremental of fluid content (ξ). The mechanical variables (stress or strain) can be related with one of the fluid quantity (pore pressure or fluid content) to form independent variable and therefore mathematical equations. For the particular case of Earth tides, is convenient to express the pore elastic equations in terms of stress and pore pressure, also termed pure stiffness formulation

$$\sigma_{ij} = \left(K_u - \frac{2G}{3} \right) \delta_{ij} \epsilon + 2G \epsilon_{ij} - \alpha M \delta_{ij} \xi \quad (1)$$

and

$$p_f = M(-\alpha \epsilon + \xi), \quad (2)$$

where α is the Biot poroelastic coefficient, K_u is the undrained bulk modulus, G is the shear modulus, ϵ is the volumetric strain ($\epsilon = \epsilon_{xx} + \epsilon_{yy} + \epsilon_{zz}$), δ_{ij} is the Kronecker delta and M is the Biot modulus which is defined as,

$$\frac{1}{M} = \frac{n}{K_f} + \frac{(1-\alpha)(\alpha-n)}{K} = \frac{\alpha}{BK_u}, \quad (3)$$

where n is the porosity, K_f is the bulk modulus of the fluid, K is the drained bulk modulus (related to the undrained bulk modulus as $K = K_u - \alpha^2 M$) and B is the Skempton coefficient. Fluid transport is modeled with the fluid balance equation as

$$S_\epsilon \left(\frac{\partial p}{\partial t} + BK_u \frac{\partial \epsilon}{\partial t} \right) = k_{ij} \nabla^2 p_f + Q \quad (4)$$

where k_{ij} is the porous medium permeability tensor, Q represents sinks or sources, $\epsilon_{ij} = \nabla u_i$ relates strain with displacement, often preferred in simulation codes (Verruijt, 2013; Kolditz et al., 2012; Flemisch et al., 2011; Keilegavlen et al., 2021), and S_ϵ is the specific storage at constant strain. S_ϵ is related to the Biot modulus as

$$S_\epsilon = \frac{1}{M}, \quad (5)$$

Equations 1, 2 and 4 can be solved in a coupled manner with appropriate boundary conditions and represent the elastic deformation and fluid movement in a porous medium.

2.2 Analytical solution

When uniaxial-vertical strain and zero incremental vertical stress are assumed (this occurs only when one of the principal stresses is non-zero and the stress does not change with depth), the subsurface is mechanically restricted to move only in the vertical direction, e.g., land surface subsidence due to consolidation occurs primarily in the vertical direction (Herrera-García et al., 2021). Under such conditions $\epsilon_{xx} = \epsilon_{yy} = 0$ and $\sigma_{zz} = 0$ which leads to a simplified version of equations 1 and 2 as

$$\sigma_{zz} = 0 = \left(K + \frac{4G}{3} \right) \epsilon_{zz} - \alpha p_f \quad (6)$$

and

$$p_f = M(-\alpha \epsilon_{zz} + \xi). \quad (7)$$

Combining 6 and 7 to eliminate ϵ_{zz} gives

$$\xi = S p_f, \quad (8)$$

where

$$S = \frac{1}{M} + \frac{3\alpha^2}{3K + 4G}. \quad (9)$$

This is the definition of storage coefficient in hydrology (Cheng, 2016; Verruijt, 2013; Wang, 2017). The specific storage, S_s , is obtained when the specific weight of the fluid is considered as

$$S_s = S \rho_f g, \quad (10)$$

where ρ_f is the density of the filling fluid and g Earth's gravitational acceleration constant.

With this derivation, we stress the conceptual difference between the specific storage at constant strain (equation 5) and the storage coefficient with uniaxial strain (equation 9). Please note that S approaches S_ϵ when $K \gg K_f$, such as when grains are less compressible than water, e.g. sand or gravel (Verruijt & Van Baars, 2007; Lambe & Whitman, 1991; Freeze & Cherry, 1979).

Hydraulic head can be used as a proxy for pore pressure in equation 4, $h = p\rho_f^{-1}g^{-1}$. Moreover, in a confined aquifer with a constant thickness H_a , hydraulic conductivity can be express in terms of transmissivity ($T = k_a H_a$) and specific storage at constant strain in terms of storativity at constant strain $S_{\epsilon,t} = S_\epsilon H_a$ as (Cheng, 2016; Verruijt, 2013; Wang, 2017),

$$S_{\epsilon,t} \left(\frac{\partial h}{\partial t} + \frac{BK_u}{\rho_f g} \frac{\partial \epsilon}{\partial t} \right) = T \left[\frac{\partial^2 h}{\partial x^2} + \frac{\partial^2 h}{\partial y^2} + \frac{\partial^2 h}{\partial z^2} \right] + Q. \quad (11)$$

For practical reasons, equation 11 can be reformulated into cylindrical coordinates assuming only radial flow (C. Jacob & Lohman, 1952; C. E. Jacob, 1946), also vertical leakage can be included in the sink/source in terms of hydraulic conductivity of the layer on top (k_l) and thickness of such layer (H_l) expecting $k_a k_l^{-1} \gg 1$ as $Q = k_l h H_l^{-1}$,

$$S_{\epsilon,t} \left(\frac{\partial h}{\partial t} + \frac{BK_u}{\rho_f g} \frac{\partial \epsilon}{\partial t} \right) = T \left[\frac{\partial^2 h}{\partial r^2} + \frac{1}{r} \frac{\partial h}{\partial r} \right] + \frac{k_l}{H_l} h. \quad (12)$$

In this work we use the terms aquifer and aquitard to reflect layers of higher and lower hydraulic conductivity, respectively, as is consistent with the terminology used in previous works. Equation 12 was used to derive analytical solutions that describe the groundwater response to Earth tides in a fully confined aquifer (Hsieh et al., 1987) and in an aquifer with vertical leakage (Wang et al., 2018). A detailed derivation of the more versatile leaky solution is presented in Wang et al. (2018), but is also included in Appendix A of this work. The solution describes the water level in a well (h_w) in terms of the hydraulic conductivity of the aquifer (k_a), hydraulic conductivity of the aquitard (k_l) and the specific storage at constant strain of the aquifer (S_ϵ). Fluid level changes in the well are caused by forces generated at the far field (far away from the radius of influence of the observation well). Assuming undrained conditions ($\xi = 0$, in equation 2) and assuming $\alpha = 1$ representing unconsolidated systems such changes can be quantify as

$$p = -M\epsilon_G, \quad (13)$$

where ϵ_G is a external gravitational strain. The change of water level in a well due to an areal strain is graphically shown in Figure 1a and 1b for two given times from $t_0 = 0$ to $t = t$ with gravitational strains from $\epsilon_G = 0$ to $\epsilon_G = \epsilon_G(t)$.

The amplitude ratio and phase shift between the piezometric head at a distance from the well beyond its radius of influence and the water level in the well are expressed as (Hsieh et al., 1987),

$$A = \left| h_w / \frac{BK_u \epsilon_0}{\rho g} \right| = \left| h_w \alpha / \frac{M \epsilon_0}{\rho g} \right| \quad (14)$$

and

$$\Delta\phi = \arg \left(h_w / \frac{BK_u \epsilon_0}{\rho g} \right) = \arg \left(h_w \alpha / \frac{M \epsilon_0}{\rho g} \right). \quad (15)$$

Here, ϵ_0 is the amplitude of the volumetric strain signal, which can be obtained from software based on tidal catalogs, e.g. PyGtide (Rau, 2018), ETERNA PREDICT (Wenzel, 1996), *TSoft* (Van Camp & Vauterin, 2005). The analytical solution is subject to the assumptions under which it was derived: (1) undrained conditions, (2) the confining layer has negligible specific storage, (3) the flow is horizontal in the aquifer, (4) the well is represented by a line with length matching the aquifer extent, (5) the deformation is only vertical, (6) no gravity.

Equations 14 and 15 can be inverted to estimate constant values of equation 12 using any approach suitable for non-linear algorithm estimation (gradient methods), e.g. least squares (Rau, Cuthbert, Acworth, & Blum, 2020). In fact, this approach has been used to estimate aquifer hydraulic conductivity, specific storage and aquitard leakage from

the amplitude and phase response of groundwater to Earth tides (Rau, Cuthbert, Acworth, & Blum, 2020). However, estimating three parameters from two inputs leaves the problem under-determined and leads to non-unique estimates. We note that neither the implications of the assumptions nor the non-uniqueness problem have been investigated for practical use of this solution.

Gradient methods such as the *Levenburg-Marquardt* often use in least-squares to numerically search for the nearest (local) minimum to the given initial condition and are readily implemented in SciPy (Virtanen et al., 2020). The obtained solution from the function fitting model finds the local minimum and depends on the initial guess. To investigate the impact of non-uniqueness by the initial conditions on the parameter estimation of Wang et al. (2018), we systematically explore the solution space of a fitting function. The fitting function was formulated as

$$FO_{Amplitude} = A_{obs} - A(k_a, S_\epsilon, k_l) \quad (16)$$

and

$$FO_{Phase} = \phi_{obs} - \Delta\phi(k_a, S_\epsilon, k_l) \quad (17)$$

where $A(k_a, S_\epsilon, k_l)$ and $\Delta\phi(k_a, S_\epsilon, k_l)$ are equation 14 and 15. The aquifer thickness and aquitard depth were arbitrarily defined to be 1 m and 100 m, respectively; the radius of the well to 0.2 m and Earth tide frequency of 1.93 cpd; A_{obs} and ϕ_{obs} are objective amplitude ratio and phase shift values given by the user.

The least-squares solver minimizes the difference between $A_{obs} - A(k_a, S_\epsilon, k_l)$ and $\phi_{obs} - \Delta\phi(k_a, S_\epsilon, k_l)$ of equations 16 and 17 by iterating through a combination of values of k_a , S_ϵ and k_l . An array consisting of discrete values within realistic ranges for amplitude ratio ($0.001 \leq A \leq 1$) and phase ($-90^\circ \leq \Delta\phi \leq 90^\circ$) were generated. For each pair of amplitude ratio and phase shift, the solution space was solved using least-squares of SciPy. The tolerance for termination by the change of the cost function was set to be $3 \cdot 10^{-6}$ and units for 16 and 17 were set to days so as to increase the numeric values and avoid errors. The sensitivity of the method was tested by generating 1000 samples of k_a , S_ϵ and k_l generated by a random log uniform distribution ranging from $1 \cdot 10^{-7} \leq k_a \leq 1 \cdot 10^{-3} \text{ ms}^{-1}$, $1 \cdot 10^{-7} \leq S_\epsilon \leq 1 \cdot 10^{-5} \text{ m}^{-1}$ and $1 \cdot 10^{-8} \leq k_l \leq 1 \cdot 10^{-4} \text{ ms}^{-1}$. Each trio of samples was set as initial condition in equation 16 and 17. Starting from different initial values allows the solver to find potentially different local minima. The outputs were stored and the maximal difference between each estimated property was used as a proxy for non-uniqueness. This approach allows identification of values within the solution space where non-uniqueness is an issue.

2.3 Numerical model

The generic equations presented in Section 2.1 can be solved analytically for specific boundary conditions (Hsieh et al., 1987) but have not been solved numerically in the context of Earth tides. Here, we develop a novel numerical approach for simulating the groundwater response to Earth tides. This allows a more realistic physical representation compared to the limiting assumptions of the analytical solution presented in Section 2.2 and advances the previous study by (Wang & Manga, 2021). The aim is to investigate and establish validity constraints for the use of the analytical solution when interpreting the groundwater response to Earth tides.

When modeling Earth tides, an external gravitational strain $\epsilon_G(x, y, z, t)$ is applied to deform the Earth's crust and the resulting fluid pressure $p_f(x, y, z, t)$, and displacement vector $u_{ii}(x, y, z, t)$ is calculated. Under the free surface condition, the normal stress along the radius is zero. Hence, gravitational strain can be decomposed into its verti-

cal $\epsilon_h(x, y, t)$ and horizontal component $\epsilon_v(z, t)$ (Agnew, 2005),

$$\epsilon_G(x, y, t) = \epsilon_h(x, y, t) + \epsilon_v(z, t). \quad (18)$$

Earth tides induce an *eigenstrain*, i.e., a strain that does not result directly from an applied force. Qu and Cherkaoui (2006) describes the differences and relationships between total, elastic and eigenstrains. To simulate the effect in a realistic well-aquifer system, in which the hydraulic and geomechanical properties of the material may vary in space, we applied vertical and horizontal strain as displacement boundary conditions. This fixes the internal strain throughout the model as a function of the filling material elastic tensor as (Wang, 2017),

$$r = R : u_{rr} = \epsilon_h(x, y, t) R, \quad (19)$$

$$r = 0 : u_{rr} = 0, \quad (20)$$

and

$$z = 0 : u_{zz} = \epsilon_v(z, t) L, \quad (21)$$

$$z = -L : u_{zz} = 0, \quad (22)$$

where R and L are the horizontal and vertical lengths, respectively. A constant atmospheric pressure (i.e. drained condition) is assumed at the top of the modelling domain as

$$z = 0 : p_f = 0. \quad (23)$$

The governing equations follow the traditional Biot (1941) theory of a linear elastic, saturated and deformable porous medium with water as the fluid (Wang, 2017; Cheng, 2016). The strong form of the general equations in Subsection 2.1 can be converted into the respective weak form and discretized before solving with the finite element (FE) method. In this study, we adopt the continuum representation of an elementary volume (REV) in a porous medium. To solve the numerical system the Real Heterogeneity App (RHEA), a FE application based on the Multiphysics Object Oriented Simulation Environment (MOOSE) was used (Permann et al., 2020). A detailed description of the system of equations to be solved as well as further information of the tight coupling and numerical description of the FE implementation utilized in this study can be found in (Bastías Espejo et al., 2021; Wilkins et al., 2021, 2020). For consistency, we keep the original notation used in Bastías Espejo et al. (2021), where the field variables are the fluid pressure p_f and the displacement vector u_{ii} .

2.4 Assessing the subsurface response conditions

Within the theory of linear poroelasticity (equations 1 to 4), one can distinguish between two end-members that describe the type of pore pressure response to stresses and strains: undrained and drained. When a deformation in a porous medium occurs, under drained conditions, the rate of applied distortion is slow in relation to the ability of the porous medium to allow dissipation of the pressure wave. This results in the flow of fluid caused by the buildup of pressure differences. Under undrained conditions, the rate of applied distortion is fast enough for an instantaneous pore pressure response to external deformations and fluid cannot flow in response.

The type of subsurface response is represented by equation 2, in which ξ describes an increment of change in fluid content. Under *undrained* conditions, $\xi = 0$ and equation 2 reduces to equation 13. While under *drained* conditions $\xi \neq 0$. Hence, the confined pore pressure as a response to Earth tides can be obtained with equation 2 if the Earth tide strain (ϵ_G) is known. According to Rojstaczer and Agnew (1989), an areal strain is sufficient for depths that are relevant to hydrogeology.




Figure 1. Overview of the conceptual models used in this work. (a) Analytical model of Wang et al. (2018) when no external force is applied (b) Analytical model of Wang et al. (2018) when the confined pore pressure generated at the far field is generated and fluid flow towards the well. (c) A 1D column of the subsurface representative of the aquitard to assess the type of response. At $t = 0$ the column is equilibrium, at $t > 0$ a harmonic strain is applied which results in fluid movement in and out of the column. (d) A 2D model of the aquifer bounded by a aquitard and connected to a well. Earth tide strain is applied which moves fluid towards a well that is numerically modeled.

For Earth tides, the applied strain depends on the frequency of the harmonic and the type of response is a function of the hydro-geomechanical subsurface properties as well as depth. To assess the type of response under realistic conditions, we numerically modeled an infinitely long 1D (5000 m) section of the subsurface (Figure 1c) using a harmonic function as displacement boundary condition as follows

$$z = 0, \epsilon_{M2} = \epsilon_0 \cdot \sin[2\pi f_{M2} t]. \quad (24)$$

Here, ϵ_0 is the amplitude of the Earth strain, f_{M2} is the frequency of the M_2 component and t is the time in days. We computed the increment of fluid content, ξ , over depth $0 \leq z \leq 1000$ m and repeated the calculations by setting assumed, but realistic discrete values of specific storage at constant strain S_ϵ , ($1 \cdot 10^{-7} m^{-1}$, $1 \cdot 10^{-6} m^{-1}$ and $1 \cdot 10^{-5} m^{-1}$), and bulk modulus K , ($1 \cdot 10^9 Pa$, $1 \cdot 10^{10} Pa$ and $1 \cdot 10^{11} Pa$), and continue values of hydraulic conductivity of the aquifer, $1 \cdot 10^{-7} \leq k_a \leq 1 \cdot 10^{-3} ms^{-1}$ within the

domain. These values represent realistic conditions as reported in the geoscience literature (Das & Das, 2008; Wang, 2017; Cheng, 2016; Lade, 2001).

When analyzing the groundwater response to Earth tides, undrained conditions have to be given for the analytical solution to be valid (Appendix A). However, the type of response to Earth tides has not been assessed before and is therefore unknown. To assess whether the subsurface response is sufficiently undrained, we can use equation 2 assuming $\alpha = 1$. Under undrained conditions $\xi = 0$, such condition can be assumed when $\epsilon \gg \xi$. Hence, the effect of ξ can be neglected in equation 2.

2.5 Numerical model of a coupled well-aquifer system

To investigate the limitations of the analytical model presented in Section 2.2, a 2D axial-symmetric cylindrical model was developed. The model accounts for poro elastic aquifer (Section 2.1) bounded by a low permeable aquitard on top and by a rigid aquiclude on the bottom. Gravity and horizontal flows are allowed (Figure 1d). Boundary conditions are set as described in Section 2.5. The applied Earth strain (ϵ_G) was calculated theoretically with PyGtide (Rau, 2018), a Python wrapper for ETERNA PREDICT 3.4. We chose the city of Berlin (Germany) and a signal frequency of 2 cpd for simplicity as it closely resembles M_2 with a duration of 30 days. While the location is arbitrary, it does not change the conclusions because the context of this study is generic.

The borehole-subsurface system is modeled as a 1D element outside the 2D system. To relate the porous medium and the borehole-subsurface, the boundary at $r = 0$ is modeled as a free drainage boundary, i.e., a sink boundary where the flux is computed in function of the pressure at $r = 0$ ($P_{r=0}$) and at the bottom of the borehole-subsurface (P_w)

$$r = 0, -101 \leq z \leq 100, \dot{m}_f = C(p_f - p_{r=0}), \quad (25)$$

where \dot{m}_f is the mass flux, C the conductance (i.e., how efficiently fluid is transported through a boundary) between the borehole-subsurface and the model. For this study $C = 10^{-3} \text{ m}^2 \text{ s}^{-1}$ which is high enough to ensure that $p_f = p_{r=0}$ at the end of each non-linear iteration.

As a result, the mass flux through the boundary between the model and the well is computed in every non-linear iteration, which fixes the pore pressure at the boundary for the next iteration. This way, the fluid level in the well is tightly coupled to the pressure at the well boundary of the model as the fluid level in the well is computed in the same Jacobian matrix with the numerical model and is computed as,

$$\frac{dh_f}{dt} = \frac{\dot{m}_f A_c}{\rho_f A_w}. \quad (26)$$

Here, h_f represents the water level in the well ($h_f = p_f g^{-1} \rho_f^{-1}$), A_c is the external area of a cylinder and A_w is the inner area of a cylinder. Since the model is linear elastic, typically, only two non-linear iterations are needed.

The model domain is $R = 5000$ m long in the r direction and $L = 101$ m in depth in the z direction. The aquitard is 100 m thick, whereas the aquifer is 1 m thick, and we assume that the well is screened throughout this unit. The 101 m long well is located at the left boundary of the modeling domain and the well has $r_w = 0.2$ m of radius (Figure 1d). The geometry complies with previous studies (Hsieh et al., 1987; Wang et al., 2018) and therefore enables a comparison. The finite elements were discretized using the built-in mesh generator of MOOSE and the element size increases logarithmically along the r -axis away from the well. The mesh is vertically and logarithmically discretized 5 times across the aquifer, 20 times across the top layer and 100 times in the horizontal direction. The material properties of the model are summarized in Table 1. The values

of Table 1 were assumed in previous studies (Wang et al., 2018) and extracted from literature (Das & Das, 2008; Wang, 2017; Cheng, 2016; Lade, 2001).

The initial pore pressure condition is set as $p_f^0 = -\rho_f g z$ and the effective initial stress as $\sigma_{zz}^0 = (\rho_s - \alpha \rho_f) g z$, where σ_{zz}^0 is the vertical component of the effective stress at time zero. Again, we apply a harmonic displacement function with the M_2 frequency computed with a tidal catalog, the amplitude of the strain is $\epsilon_0 = 1.2 \cdot 10^{-8}$. The model runs until it reaches quasi steady-state, at which point the well physics as well as tidal forcing as boundary conditions are activated. This approach minimizes potential numerical overshooting produced by the free drainage boundary between the porous medium and the well. We verify this numerical implementation using the analytical solution of Wang et al. (2018) (Subsection 2.2) with the aquitard permeability set to zero, i.e., the model represents only one layer.

3 Results and discussion

3.1 Analytical solutions

Previous research has used the analytical solutions by Hsieh et al. (1987), H. F. Wang (2000) and Wang et al. (2018) to estimate hydraulic properties for negative and positive phase shifts between groundwater and Earth tides, respectively. We note that Hsieh et al. (1987) and Wang et al. (2018) requires undrained conditions whereas H. F. Wang (2000) assumes drained conditions. The validity conditions for these assumptions have not been investigated for Earth tide frequencies. For drained conditions the relationship between stress and strain is no longer linear, as porepressure also plays a role bearing loads, i.e. see Equation 2. Furthermore, while H. F. Wang (2000) considers vertical flow in a one dimensional poroelastic aquifer, it neglects the influence of an observation well. As shown in Figure 2, a well generates phase shifts between the confined far distance porepressure and the water level in the well as the fluid requires time to move in and out of the well. Strictly speaking, this solution was derived for surface loads, such as exerted from atmospheric pressure, but not for Earth tide strains. These aspects illustrate that H. F. Wang (2000) has limited use when estimating hydraulic properties from the groundwater response to Earth tides.

Wang et al. (2018) provides an extended formulation to Hsieh et al. (1987) considering vertical aquitard leakage accounting for both negative and positive phase shifts. It is useful to illustrate the solution space of Wang et al. (2018) by providing an overview of amplitude ratios and phase shifts (Equations 14 and 15) as a function of realistic ranges of the aquifer hydraulic conductivity (k_a) and specific storage at constant strain (S_ϵ) as well as discrete values of leakage, see Figure 2. Note that this is based on the dominant harmonic signal frequency of 2 cpd, a well and screen radius of 0.2 m, a screen length of 1 m and an aquitard thickness of 100 m. The first row, Figure 2a and 2b, shows the case where there is no vertical leakage leading to negative phase shifts only. We confirm the reports by Wang et al. (2018) that the analytical solution matches the previous solution by Hsieh et al. (1987) when the aquitard hydraulic conductivity is set to zero.

The solution space shows that vertical leakage causes positive phase shifts at relatively high aquifer hydraulic conductivity, i.e., $k_a > 1 \cdot 10^{-5} \text{ ms}^{-1}$ in Figure 2d. This threshold is even more clear for vertical leakage larger than $k_l > 1 \cdot 10^{-6} \text{ ms}^{-1}$ where the transition to positive phase shift is almost linear. Moreover, in Figures 2d and 2f, the phase shift behavior is very similar for the lower part of the specific storage at constant strain under study ($S_\epsilon < 1 \cdot 10^{-5} \text{ m}^{-1}$). A similar case is observed in Figures 2c and 2e where the amplitude response of the analytical solution shows very similar results.

The solution space illustrated in Figure 2 shows that the solution is under-determined when subsurface parameters are estimated, because three hydraulic properties (hydraulic

Table 1. Overview of the hydraulic and mechanical properties of the numerical model.

Property	Acronyms	Value	Unit	Reference
Aquitard hydraulic conductivity	k_l	$1 \cdot 10^{-7} \leq k_l \leq 10^{-4}$	$m \ s^{-1}$	(Wang, 2017; Cheng, 2016)
Aquitard specific storage at constant strain	$S_{\epsilon,l}$	$1 \cdot 10^{-7}, 1 \cdot 10^{-6}, 1 \cdot 10^{-5}$	m^{-1}	(Wang, 2017; Cheng, 2016)
Aquitard bulk modulus	K_l	10	GPa	(Das & Das, 2008)
Aquitard Poisson's ratio	ν_l	0.25	-	(Das & Das, 2008)
Aquitard Biot coefficient	a_l	1	-	(Wang, 2017; Cheng, 2016)
Aquifer hydraulic conductivity	k_a	$1 \cdot 10^{-3}, 1 \cdot 10^{-4}, 1 \cdot 10^{-5}$	$m \ s^{-1}$	(Wang, 2017; Cheng, 2016)
Aquifer specific storage at constant strain	$S_{\epsilon,a}$	$1 \cdot 10^{-7}, 1 \cdot 10^{-6}, 1 \cdot 10^{-5}$	m^{-1}	(Wang, 2017; Cheng, 2016)
Aquifer bulk modulus	K_a	10	GPa	(Das & Das, 2008)
Aquifer Poisson's ratio	ν_a	0.25	-	(Das & Das, 2008)
Aquifer Biot coefficient	a_a	1	-	(Das & Das, 2008)
Skeleton density	ρ_s	2000	$kg \ m^{-3}$	(Wang, 2017; Cheng, 2016)
Bulk modulus of the water	K_f	2.2	GPa	(Wang, 2017; Cheng, 2016)
Water density	ρ_f	1000	$kg \ m^{-3}$	(Wang, 2017; Cheng, 2016)

The subscript l and a refer to aquitard and aquifer, respectively.

creases as the phase shift approaches 0° . For values higher than zero degrees the sensitivity decreases again until approximately 40° where it starts to increase again (Figure 3a). The highest sensitivity is found around amplitude ratio of one and positive phase shift. Situations where the amplitude ratio is one and the phase shift much higher than zero are not realistic and should be disregarded.

Specific storage at constant strain shows a high contrast in solution variability with values that are very close to $\Delta S_\epsilon = 1 \cdot 10^{-5} m^{-1}$ for most of the solution space (Figure 3b). At low phase shifts ($\Delta\phi < -70^\circ$) the variability significantly reduces to $\Delta S_\epsilon = 1 \cdot 10^{-7} m^{-1}$. In practice, most of the realistic cases will fall within the high variability zone. Vertical leakage shows relatively low sensitivity where the phase shift is negative ($\Delta k_l < 5 \cdot 10^{-5} ms^{-1}$, Figure 3c). However, at positive phase shifts the variability increases up to two orders of magnitude, demonstrating the effect of the phase shift on vertical leakage.

In the illustrated case, the sensitivity of the specific storage at constant strain is constant throughout the solution space and therefore its initial value does not play a significant role on finding different solutions. Negative phase shifts show a low sensitivity to the initial condition and will likely result in an accurate inversion of the hydraulic properties without a priori knowledge of the subsurface properties as mentioned in section 2.2. For positive phase shifts a handle on at least one of the properties is necessary as the vertical leakage significantly increases its variability. Further, the hydraulic conductivity increases its variability towards high amplitudes which is the range where Earth tide methods work best. Overall, this complies with the previous finding that positive phase shifts can robustly be interpreted as vertical leakage (Wang et al., 2018).




Figure 3. Color map exploring the solution space, i.e., the variability of parameters as a function of the initial guess, of the under-determined problem by (Wang et al., 2018). Estimating three hydraulic properties out of two measured parameters: (a) aquifer hydraulic conductivity, (b) specific storage at constant strain, (c) aquitard hydraulic conductivity. Note that each color scale has a different range. Blue indicates less variability, whereas red means more variability of the results.

3.2 Notes on the specific storage

An interesting implication of Section 2.1 arises when $\alpha = 1$. The latter refers to systems where the compressibility of grains is small compared to the compressibility of grains, such as is the case for unconsolidated materials. Here, the specific storage at constant strain (the inverse of the *Biot* modulus, equation 3) reduces to

$$S_\epsilon = \frac{1}{M} = \frac{n}{K_f}. \quad (27)$$

Since the bulk modulus of water is known ($K_f = 2.2 \cdot 10^9 \text{ Pa}$), the porosity of the material can also be estimated from the groundwater response to Earth tides. However, for consolidated materials the Biot coefficient may be smaller than one. This can help to constrain the expected values of the specific storage at constant strain. For instance, if the subsurface material is unconsolidated and has realistic porosity values, i.e., $0.01 \leq n \leq 0.3$, then the specific storage at constant strain is constrained to

$$4.5 \cdot 10^{-8} m^{-1} \leq S_\epsilon \leq 1 \cdot 10^{-6} m^{-1}. \quad (28)$$

We note that previous studies which estimated the specific storage from the groundwater response to Earth tides have not considered the appropriate context for this property. The result is referred to as "specific storage at constant strain" (S_ϵ) and it can vary significantly from the specific storage generally used in hydrogeology (S_s , see Equation 9) (Hantush, 1960). The difference between both coefficients originates from the underlying assumptions. The specific storage at constant strain is defined in conditions in which the volume of the porous frame is maintained constant but the fluid volume is not, which induces changes in the pore volume because fluid has to be accommodated. In contrast, for the specific storage used in hydrogeology the porous frame is allowed to deform in the vertical direction. This is mathematically represented by the second term of Equation 9. Thus, when the subsurface material is much less compressible than the filling fluid and the pore space the second term of Equation 9 tends to zero because no deformation of the frame takes occurs, hence $S \approx S_\epsilon$. As demonstrated in this study, attention must be paid to the conceptual difference between these two parameters.

3.3 Numerical modeling of the groundwater response to Earth tides

The fluid continuity equation (equation 4) has been solved in previous studies assuming that the strain term $\epsilon(t)$ is known and solely time-dependent with adequate boundary conditions. This equation is an *inhomogenous* diffusion equation for which the change of volumetric strain is mathematically equivalent to a sink/source in the aquifer storage term. Therefore, changes of strain result in changes of porepressure in the entire model domain. When mechanical coupling is included, the continuity equation needs to be coupled to the state of stress, hence the strain is tightly coupled to porepressure. Thus, the strain term in equation 4 is no longer uniform over the entire model and may vary depending on the amount of change of fluid. For instance, changes in porepressure (for earth tides within the radius of influence of the well) induces changes in the volumetric strain, which generate drained conditions (Section 3.4). Therefore, assuming that the applied strain is constant within the model domain is inaccurate for our purposes since, as explained before, the strain is function of the porepressure. Another common way to express the coupling between porepressure and strain is by rearranging Equations 1 and 2 as

$$\epsilon = \frac{1}{K} \sigma + \frac{\alpha}{K} p_f. \quad (29)$$

The relative movement of celestial bodies in relation to Earth induces variations in the gravitational force which results in small deformation of the Earth's crust. Such deformations are not caused by an applied stress. In continuum mechanics, this problem is known as *eigenstrain*, and it is very common in heat transport, e.g., dilatation caused by heating of materials. The relationship between deformation and *eigenstrain* can be obtained experimentally leading to a constitutive model (Qu & Cherkaoui, 2006). In this work we apply a simpler approach. As FE implementation typically requires displacement or load as boundary conditions, we set displacement as boundary condition and directly applied the strain obtained from an Earth tide catalog multiplied with the length of the model, i.e., $u_{ii} = \epsilon_{ii} L$.

While this approach is convenient it has limitations. If the mechanical properties change over the modeling domain (composite material), the displacement will not be uni-

formly distributed across the domain and therefore the resulting strain will also be non-uniform. This would produce larger displacements in soft layers resulting in higher porepressure. One way to solve this problem is to assume vertical heterogeneity and to apply the total volumetric strain only at the horizontal boundaries. This would result in a uniform displacement distribution in the horizontal axis and therefore result in an appropriate porepressure response. We note that the effects of distributed mechanical heterogeneity are not further explored in this work.

Initialization of the numerical model is not trivial since the initial hydrostatic and mechanical states (initial porepressure and stresses) has to be in equilibrium (Settari & Walters, 2001). This challenge applies in particular for heterogeneous distributions of material properties and transient boundary conditions. Achieving mechanical equilibrium at time $t = 0$ is difficult and may in most cases require a separate initialization step during the simulation (Chen et al., 2009). We recommend to first simulate steady-state conditions which generates the stress and porepressure distribution within the modeling domain.

From a numerical point of view, the simulator is setting the force balance as an approximation, i.e., $\nabla\sigma = 0$. In practice, a non-linear step is finished when the force balance falls below a threshold close to zero but residual errors always remain. Earth tides generate only small changes in porepressure which are close to the residual error. For example, if the acceptable error is $e = 1 \text{ Pam}^{-2}$, then in our case the area is 5050000 m^2 leading to total residuals up to $R \approx 5050 \text{ kPa}$ at the bottom of the model. Since Earth tides generate porepressure change in smaller magnitude, minimizing the error is an important consideration when modeling. Numerical modeling of Earth tides therefore requires attention to decreasing the tolerance of the numerical solver (e.g., by increasing the number of linear steps), increasing space discretization (e.g., by increasing the size of the Jacobian matrix) or decreasing time discretization (e.g., by increasing the number of time steps).

3.4 Are conditions for the M_2 Earth tide drained or undrained?

When a stress is applied to an undrained subsurface system, the load is shared by the bulk material, the grains and the pore fluid. The balance between these three responses results in instantaneous deformation of the pore space and a change in fluid pressure. If the rate of the applied deformation is slow enough then fluid can flow out of the system which reduces the porepressure. The balance between the rate of Earth tide stress and realistic hydro-geomechanical subsurface properties is rarely known. Moreover, fluid movement (i.e., drained conditions) may be given leading to $\xi \neq 0$. Under such conditions the assumptions of the analytical solutions are violated potentially leading to errors when interpreting the groundwater level response to Earth tides.

To assess the conditions under which an undrained response occurs, we numerically simulate a 1D vertical column with depth $0 \leq z \leq 5000 \text{ m}$ (Figure 1b) and with a range of realistic hydraulic and geomechanical properties. Equation (2) can be solved for fluid quantity (ξ) assuming the worst scenario ($\epsilon_G = 1 \cdot 10^{-8}$ corresponding to a low tide amplitude) and $\alpha = 1$,

$$\xi = \frac{p_f}{M} - \epsilon_G = S_\epsilon p_f - \epsilon_G, \quad (30)$$

Figure 4 shows the results of our numerical model which calculates ξ up to 1000 m depth and for a range of realistic hydraulic properties as well as discrete values of the bulk modulus. As typical Earth tide amplitudes vary between $1 \cdot 10^{-7} \leq \epsilon_G \leq 1 \cdot 10^{-8}$ (Rojstaczer & Agnew, 1989), we define

$$\xi < 5 \cdot 10^{-11} \quad (31)$$

as a condition for an undrained response for which the analytical solution is valid, i.e., no porepressure changes occur under this value. This is highlighted in Figure 4 and allows an assessment of the conditions for which the analytical solution should be valid.




Figure 4. Change of fluid content ξ over depth and aquitard hydraulic conductivity for a 1D column (Figure 1b) and Earth tide forcing with M_2 frequency. Rows correspond to different values of specific storage whereas columns are representative for different bulk moduli, e.g., clay (a, d, g), sand (b, e, h) and hard rock (c, f, i). Values of ξ can be used to infer the depth at which the system response is undrained, i.e., where application of the analytical solution (Equations 14 and 15) is valid. Value ranges of validity are delineated by the dashed line.

Figure 4 shows that undrained conditions are more likely the deeper a system. Further, when the hydraulic conductivity of the leaky layer (k_l) increases, the system behaves more drained. This is expected as the system becomes more permeable and therefore allows flow in response to pressure gradients. This results in fluid movement which causes increased drainage. Similarly, as the specific storage at constant strain increases (rows of plots in Figure 4) the level of drainage decreases. This is because as S_ϵ increases the volume of fluid that the system contains due to deformation increases leading to less fluid moving out of the system. This can also be explained using Equation 4 when dividing by S_ϵ

$$\left(\frac{\partial p}{\partial t} + BK_u \frac{\partial \epsilon}{\partial t}\right) = \frac{k}{S_\epsilon} \nabla^2 p + \frac{Q}{S_\epsilon}. \quad (32)$$

Equation 32 illustrates that the hydraulic diffusivity of a system (kS_ϵ^{-1}) decreases with the increase of S_ϵ .

As the bulk modulus (K) increases, see columns in Figure 4, the system becomes more drained. An explanation for this is that as the filling material becomes stiffer, the mechanical coupling becomes less relevant and the system approaches an incompressible porous skeleton. Under such conditions, only a drained response is allowed and an instantaneous pneumatic response of the system is no longer possible. This can also be explained by revisiting the definition of the Skempton coefficient (B). Assuming $\alpha = 1$, then

$$B = \frac{K_f}{K_f + \phi K} \quad (33)$$

which illustrates that when the bulk modulus increases B decreases. This results in a reduction of the overall storativity of the system and consequently also drainage. Another way to understand this result is by considering the coupling of equations. For this simulation we assumed mechanical stress balance as follows

$$\frac{\partial \sigma_{zz}}{\partial z} = 0. \quad (34)$$

Here, Equation 1 must remain constant when the total stress increases (first two terms of the Equation 1) thus the amount of fluid leaving the system must increase (third term of the equation 1).

In general, a larger porosity will increase the value of the specific storage at constant strain, which will decrease the level of drainage. Our assessment shows that when the hydraulic conductivity of the leaky layer exceeds 10^{-5} ms^{-1} , this leads to drained conditions and could result in errors when the analytical solution is used to estimate the properties of the aquifer. However, it is worth noting that the level of drainage depends on the geomechanical properties of the system, as well as depth and frequency of the signal. The amplitude of the signal, ϵ_0 , for field measurements, as higher amplitudes will generate higher confined porepressure and facilitate detection of fluid level changes inside the observation well.

As shown in Figure 4, the level of confinement depends on the hydraulic and geomechanical properties of the subsurface under consideration. Consequently, defining conditions under which an undrained response exists depends on the particular field conditions, e.g., depth of the borehole and some knowledge of the subsurface properties. Figure 4 can be used as a preliminary guide for assessing whether or not it is appropriate to apply the analytical solution for interpreting the groundwater level response to Earth tides.

3.5 Validity and limits of analytical Earth tide interpretations

Determining subsurface properties from Earth tide responses requires system confinement as a basic condition. To study the effects of a realistic well-aquifer system and

the effect of (un)drained conditions, the level of confinement is gradually relaxed in a layered 2D model in this section. Figure 5 shows the results from our numerical model (Section 2.5) compared to the analytical solution without vertical leakage ($k_l = 0 \text{ ms}^{-1}$) for a tidal signal with 2 cpd frequency (Section 2.2). The good agreement of amplitude ratios and phase differences verifies our coupled numerical modeling approach. This allows a rigorous hydraulic and geomechanical assessment of how realistic conditions (e.g., subsurface layered heterogeneity) affects the groundwater response to Earth tides.




Figure 5. Verification of the 2D numerical model against Hsieh et al. (1987) for a harmonic forcing signal with 2 cpd frequency. Here, the simulation of the hydraulic conductivity of the leaky layer was set to zero.

Numerical simulations consider discrete values of the hydraulic conductivity of the aquifer (10^{-3} ms^{-1} , 10^{-4} ms^{-1} and 10^{-5} ms^{-1}) and varying values of the aquitard, $10^{-7} \leq k_l \leq 10^{-4}$ (in ms^{-1}). In addition, discrete values of specific storage at constant strain (10^{-5} m^{-1} , 10^{-6} m^{-1} and 10^{-7} m^{-1}) were investigated. For detailed information of all the material parameters used in the simulation please refer to Table 1.

The effect of the amplitude ratio and the phase shift due to leakage of the aquitard are shown in figure 6. The columns represent values of aquifer hydraulic conductivity (k_a). The first row shows the effect on the amplitude ratio (A) and the second column the effect of the phase shift (ϕ) over different levels of aquitard confinement (k_l). Each line in the figure 6 correspond to the three discrete simulated values of the specific storage at constant strain (S_ϵ). Simulations are shown with marked lines while the analytical solution of Wang et al. (2018) is shown with dashed lines.

The level of drained conditions can be assessed in conjunction with figure 4 for the three specific storage at constant strain simulated here (figure 4b, 4e and 4h). For example, at 100 m depth (which is the thickness of the aquitard in the simulations) and $S_\epsilon = 10^{-7} \text{ m}^{-1}$ (Figure 4b), the system shows drained conditions within the entire range of confinement ($10^{-7} \leq k_l \leq 10^{-4} \text{ ms}^{-1}$, see the blue triangle markers in Figure 6). Therefore, the simulated amplitude under these conditions is somewhat lower and the




Figure 6. Comparison of the amplitude ratios and phase shifts obtained from numerical modeling and the analytical solution by Wang et al. (2018).

phase shift higher compared to the analytical solution. This results in an underestimation of the hydraulic properties of the aquifer (k_a and S_e) or overestimation of leakage from the aquitard (k_l) when the analytical solution is used.

When the specific storage at constant strain of the aquifer is $S_e = 10^{-6} m^{-1}$, at 100 m depth, the system is in a transition zone between positive and negative change of fluid content when $k_l = 10^{-7} ms^{-1}$ (Figure 4e). Since the simulated amplitude ratio and phase shift match the analytical solution, the system can still be assumed as undrained within this transition zone. However, for higher levels of leakage ($k_l > 10^{-7} ms^{-1}$), the system is outside this transition zone and completely drained conditions prevail. The latter leads to significant differences between numerical and analytical results.

Similar results are observed when the specific storage at constant strain of the aquifer is $S_e = 10^{-5} m^{-1}$. When the level of leakage is $k_l \leq 5 \cdot 10^{-5} ms^{-1}$ the system is undrained or in the transition zone and the numerical results comply with the analytical solution. For lower levels of confinement (i.e. $k_l > 5 \cdot 10^{-5} ms^{-1}$), the system becomes drained and the simulation results, once again, differ compared to the analytical solution.

In the particular case when the hydraulic conductivity of the aquifer is $k_a = 10^{-5} ms^{-1}$, the numerical results do not comply with the ones obtained with the analytical solution even under undrained conditions (Figure 6c and 6f). As the hydraulic conductivity of the aquifer decreases, the finite time to move fluid in or out of the well increases. Hence, it is likely that the fluid velocity is much more influenced by high gradients generated by the drained top boundary rather than by the gradients produced inside the open well under such conditions.

In all three columns of Figure 4, as the level of confinement provided by the aquitard decreases, the simulated results of phase shift tend towards the same value (90° for the

simulated system). This means that, as the drainage from the aquitard increases, the effect of the top drained boundary over the porepressure in the aquifer increases. The same effect is observable on the amplitude ratio, where the final value of the amplitude ratio is the same in every specific storage at constant strain under study. This effect indicates that the hydraulic conductivity of the aquifer loses relevance as the drainage from the aquitard increases. And, therefore, if the system is draining, at low levels of confinements ($k_l > 5 \cdot 10^{-5} \text{ ms}^{-1}$), the groundwater level measured in the field can potentially result in very similar values regardless of the aquifer hydraulic conductivity.

The effect of drained conditions on the amplitude ratio and phase shift can be better understood when streamlines (i.e., the Darcy velocity field) of the system are plotted. Figure 7 shows streamlines in an area close to the open well when the amplitude of the Earth tide strain is at maximum. This provides understanding of how flow paths change as the level of confinement decreases at fixed aquifer specific storage at constant strain ($S_\epsilon = 10^{-6} \text{ m}^{-1}$) and hydraulic conductivity ($k_a = 10^{-4} \text{ ms}^{-1}$). At the high confinement ($k_l = 10^{-7} \text{ ms}^{-1}$) the flow within the aquifer is horizontal and porepressure gradients are directed towards the well. This complies with the assumption of horizontal flow inherent to the analytical solution. As confinement decreases (i.e., increasing leakage of the aquitard), the velocity field shows increasing flow in the vertical direction through layers which reduces the radius of influence of the well. With the smallest confinement investigated (Figure 6c), vertical flow dominates in the aquifer and almost no horizontal flow is observable. This shows that the pressure wave produced by the open top boundary has strong effects on the amplitude ratio and phase shift at low confinement and dampens the porepressure signal generated by Earth tides.




Figure 7. Streamlines show the velocity field towards the observation well during maximum Earth tide strain for three different aquitards with varying hydraulic conductivities: (a) low, (b) medium, (c) high. This illustrates that the flow direction changes from horizontal to vertical as the leakage increases.

Figure 2 can be used in conjunction with the results shown in Figure 6 to assess the potential error due to requiring undrained conditions when the analytical solution is utilized. For example, assuming a typical specific storage at constant strain of $S_\epsilon = 10^{-6} \text{ m}^{-1}$, leakage of $k_l = 10^{-6} \text{ ms}^{-1}$ and hydraulic conductivity of the aquifer $k_a =$

10^{-3} ms^{-1} , the simulated amplitude ratio is 0.61 and the phase shift is 55.0° (Figure 6a). Figures 2e and 2f show that for that amplitude ratio and phase shift, the hydraulic conductivity of the aquifer is between $k_a = 3 \cdot 10^{-4} \text{ ms}^{-1} \leq k_a \leq 5 \cdot 10^{-2} \text{ ms}^{-1}$, while the specific storage at constant strain between $7 \cdot 10^{-5} \text{ m}^{-1} \leq S_\epsilon \leq 10^{-6} \text{ m}^{-1}$. This range is comparable with traditional field methods that estimate subsurface properties, for example applying hydraulic tests.

Our results show that a high specific storage at constant strain ($S_\epsilon \geq 10^{-6} \text{ m}^{-1}$) in combination with a high confinement ($k_l \leq 5 \cdot 10^{-5} \text{ ms}^{-1}$) and hydraulic conductivity of the aquifer ($k_a \geq 10^{-4} \text{ ms}^{-1}$) allow application of the analytical solution. Application to real world system further requires a high contrast in hydraulic conductivity between the layers ($k_a k_l^{-1} \geq 10^3$) with specific storage values that are typical ($\approx 10^{-6} \text{ m}^{-1}$). In reality, the confined porepressure is damped by the movement of fluid and fully undrained conditions may be rare. Any a priori knowledge of the formation (e.g., thicknesses and hydraulic properties) is key in the assessment of Earth tidal analysis, not only to have a good approximation when inverting equations, but also to approximate the level of drainage and therefore assess potential errors when the analytical solutions are utilized.

For unconsolidated systems the soil matrix is more compressible than the grains (i.e., an unconsolidated subsurface) which leads to $\alpha = 1$. Moreover, hydraulic conductivity and porosity for what can be considered an aquifer varies between $10^{-2} \text{ ms}^{-1} \leq k_a \leq 10^{-4} \text{ ms}^{-1}$ and $0.2 \leq n \leq 0.3$, respectively. This means that the specific storage at constant strain varies between $9.1 \cdot 10^{-7} \text{ m}^{-1} \leq S_\epsilon \leq 1.4 \cdot 10^{-6} \text{ m}^{-1}$ (with the bulk modulus of water, $K_f = 2.2 \cdot 10^{-9} \text{ Pa}$). Considering these ranges and given sufficiently high confinement between layers, application of the analytical solution to well fluid levels is valid. For example, this would be the case for hydraulic properties of sands and gravels overlain by clays or silts.

For consolidated systems, Earth tidal analysis poses a challenge as the Biot coefficient generally is $\alpha < 1$. In order to use the groundwater response to Earth tides, the Biot coefficient has to be known as it directly attenuates the porepressure response to strain (Equation 2). Although some values of the Biot coefficient have been reported for different rock types varying from 0.1 to 1 (Cheng, 2016), real world measurements are difficult to find in the literature (C. Wang & Zeng, 2011; Cosenza et al., 2002). Our work shows that the Biot coefficient requires estimation when the groundwater response to Earth tides is quantitatively evaluated for wells screened in consolidated systems. Hence, for real systems, this leads to the following trade-off: As deeper wells are more likely to contain Earth tide influences because undrained conditions exists, but they are also more likely consolidated, in which case an estimate of the Biot modulus is required. Overall, our results show that a presence of Earth tide components in wells that are screened in deep and unconsolidated systems are likely to have undrained conditions and are therefore suitable for interpretation.

4 Conclusions

The amplitude and phase of the groundwater response to harmonic Earth tide components can be used to estimate hydraulic conductivity and specific storage values of aquifer systems. However, this approach is based on simplified analytical solutions to the groundwater flow equation, which has various assumptions that have not been tested yet. To assess the effect of such assumptions, we present a numerical method to simulate the groundwater response to Earth tides by coupling compressible flow to geomechanics. We demonstrated that this can be solved numerically using the *Multi Object Oriented Simulation Environment* (MOOSE) and verify this using a simplified analytical solution of the groundwater flow equation. We further use simulations to assess the conditions of validity for

simplified analytical solutions when estimating hydraulic properties from the groundwater response to Earth tides.

By first focusing on the aquitard layer, we assess the subsurface response type, i.e., drained or undrained conditions, to the dominant harmonic Earth tide component at M_2 with frequency of 1.93227 cycles per day (cpd) for depths up to 5 km and a range of hydraulic conductivities. Based on typical Earth tide strains, we define that undrained conditions exist when the incremental of fluid content is smaller than $5 \cdot 10^{-11}$ for which the groundwater equation and associated analytical solution should be valid. Our results show that this is the case for specific storage at constant strain larger than $1 \cdot 10^{-6} m^{-1}$ and depths higher than 50 m for low conductivity systems ($k_a < 10^{-7} ms^{-1}$) and depths up to 1 km for high conductivity systems ($k_a \geq 10^{-3} ms^{-1}$).

We revisited previously interpretations based on analytical solutions and showed that the specific storage has been often misinterpreted. Moreover, non-uniqueness could influence estimation of values of the three hydraulic properties such as (1) aquifer hydraulic conductivity, (2) specific storage at constant strain and (3) aquitard hydraulic conductivity. A comparison between the analytical solution and a 2D two-layered aquitard-aquifer system coupled to a well shows that amplitudes and phases diverge when the hydraulic conductivity contrast between aquifer and aquitard reduces. This is caused by decreasing confinement leading to flow paths that change from horizontal to vertical as the vertical leakage increases. Applicability of the analytical solution to real-world problems requires a hydraulic conductivity contrast of at least 3 orders of magnitude.

Overall, the confined porepressure generated by Earth tide strains can be significantly attenuated by the movement of fluid through boundaries (i.e., drained conditions). Furthermore, any additional a priori knowledge about the hydraulic or geomechanical properties of the subsurface formation is crucial, if the groundwater response to Earth tides is evaluated using analytical solutions. Our numerical approach developed and documented can be extended to investigate the influence of other variables on results from analytical solutions. Finally, results obtained from the groundwater response to Earth tides should be validated with established hydraulic and geophysical methods.

Appendix A Response of well water levels to harmonic forcing

Hsieh et al. (1987) assumed unidirectional radial flow to a well which changes the water level in a well located at a boundary of the aquifer. The head gradient in the aquifer is given by the volumetric strain of an Earth tide which is assumed to be known. Later on, Wang et al. (2018) complemented Hsieh et al. (1987) work by considering a two layered system by adding a leaking term to the equation 12 expressed by

$$Q = -\frac{k_l}{H_l}h, \quad (A1)$$

with boundary conditions given by

$$t > 0, r = r_\infty : h(r, t) = h_\infty \quad (A2)$$

$$t > 0, r = r_w : h(r, t) = h_w(t) \quad (A3)$$

$$t > 0, r = r_w : 2\pi r_w T(\partial h / \partial r) = \pi r_c^2 (\partial h_w / \partial t) \quad (A4)$$

where k_l is the hydraulic conductivity of the leaky layer and H_l the thickness of the leaky layer. Wang et al. (2018) presented a solution for changes in well water levels are given by

$$h_w = \frac{i\omega S_t}{(i\omega S_t + k_l/H_l)\gamma} \left(\frac{BK_u \epsilon_0}{\rho g} \right), \quad (A5)$$

where ω is the angular frequency, $h_{w,e}$ is the change in water level in the well caused by Earth tides, ϵ_0 the amplitude of the Earth strain

$$\gamma = 1 + \left(\frac{r_c}{r_w} \right)^2 \frac{i\omega r_w}{2T\beta} \frac{K_0(\beta r_w)}{K_1(\beta r_w)}, \quad (\text{A6})$$

where r_w is the well radius, r_c is the radius of the well case, K_0 and K_1 are the modified Bessel functions of the first and second kind respectively and

$$\beta = \left(\frac{k_l}{TH_l} + \frac{i\omega S_t}{T} \right)^{0.5}. \quad (\text{A7})$$

Acknowledgments

This project has received funding from the German Research Council (DFG) grant agreement number 424795466. The authors wish to thank Dr. Andrew Wilkins for the technical support in the numerical implementation of this study.

References

- Abarca, E., Karam, H., Hemond, H. F., & Harvey, C. F. (2013). Transient groundwater dynamics in a coastal aquifer: The effects of tides, the lunar cycle, and the beach profile. *Water Resources Research*, 49(5), 2473–2488.
- Agnew, D. C. (2005). Earth tides: an introduction. *University of California, San Diego*.
- Alcaraz, M., Carrera, J., Cuello, J., Guarracino, L., & Vives, L. (2021). Determining hydraulic connectivity of the coastal aquifer system of la plata river estuary (argentina) to the ocean by analysis of aquifer response to low-frequency tidal components. *Hydrogeology Journal*, 29(4), 1587–1599.
- Allègre, V., Brodsky, E. E., Xue, L., Nale, S. M., Parker, B. L., & Cherry, J. A. (2016). Using earth-tide induced water pressure changes to measure in situ permeability: A comparison with long-term pumping tests. *Water Resources Research*, 52(4), 3113–3126.
- Bastias Espejo, J. M., Wilkins, A., Rau, G., & Blum, P. (2021). Rhea v1. 0: Enabling fully coupled simulations with hydro-geomechanical heterogeneity. *Geoscientific Model Development Discussions*, 1–21.
- Biot, M. A. (1941). General theory of three-dimensional consolidation. *Journal of applied physics*, 12(2), 155–164.
- Chen, Y., Zhou, C., & Jing, L. (2009). Modeling coupled thm processes of geological porous media with multiphase flow: theory and validation against laboratory and field scale experiments. *Computers and Geotechnics*, 36(8), 1308–1329.
- Cheng, A. H.-D. (2016). *Poroelasticity* (Vol. 27). Springer.
- Cooper Jr, H. H., Bredehoeft, J. D., & Papadopoulos, I. S. (1967). Response of a finite-diameter well to an instantaneous charge of water. *Water Resources Research*, 3(1), 263–269.
- Cosenza, P., Ghoreychi, M., De Marsily, G., Vasseur, G., & Violette, S. (2002). Theoretical prediction of poroelastic properties of argillaceous rocks from in situ specific storage coefficient. *Water Resources Research*, 38(10), 25–1.
- Cuttillo, P. A., & Bredehoeft, J. D. (2011, 7). Estimating Aquifer Properties from the Water Level Response to Earth Tides. *Ground Water*, 49(4), 600–610. Retrieved from <http://doi.wiley.com/10.1111/j.1745-6584.2010.00778.x> doi: 10.1111/j.1745-6584.2010.00778.x
- Das, B. M., & Das, B. (2008). *Advanced soil mechanics* (Vol. 270). Taylor & Francis New York.
- Flemisch, B., Darcis, M., Erbertseder, K., Faigle, B., Lauser, A., Mosthaf, K., ... others (2011). Dumux: Dune for multi-{phase, component, scale, physics,...}

- flow and transport in porous media. *Advances in Water Resources*, 34(9), 1102–1112.
- Freeze, R. A., & Cherry, J. A. (1979). *Groundwater*.
- Gao, X., Sato, K., & Horne, R. N. (2020). General solution for tidal behavior in confined and semiconfined aquifers considering skin and wellbore storage effects. *Water Resources Research*, 56(6), e2020WR027195.
- Guo, H., Brodsky, E., Goebel, T., & Cladouhos, T. (2021). Measuring fault zone and host rock hydraulic properties using tidal responses. *Geophysical Research Letters*, 48(13), e2021GL093986.
- Hantush, M. S. (1960). Modification of the theory of leaky aquifers. *Journal of Geophysical Research*, 65(11), 3713–3725.
- Herrera-García, G., Ezquerro, P., Tomás, R., Béjar-Pizarro, M., López-Vinielles, J., Rossi, M., ... others (2021). Mapping the global threat of land subsidence. *Science*, 371(6524), 34–36.
- Hsieh, P. A., Bredehoeft, J. D., & Farr, J. M. (1987). Determination of aquifer transmissivity from earth tide analysis. *Water resources research*, 23(10), 1824–1832.
- Jacob, C., & Lohman, S. (1952). Nonsteady flow to a well of constant drawdown in an extensive aquifer. *Eos, Transactions American Geophysical Union*, 33(4), 559–569.
- Jacob, C. E. (1946). Radial flow in a leaky artesian aquifer. *Eos, Transactions American Geophysical Union*, 27(2), 198–208.
- Jardani, A., Dupont, J.-P., Revil, A., Massei, N., Fournier, M., & Laignel, B. (2012). Geostatistical inverse modeling of the transmissivity field of a heterogeneous alluvial aquifer under tidal influence. *Journal of Hydrology*, 472, 287–300.
- Keilegavlen, E., Berge, R., Fumagalli, A., Starnoni, M., Stefansson, I., Varela, J., & Berre, I. (2021). Porepy: An open-source software for simulation of multiphysics processes in fractured porous media. *Computational Geosciences*, 25(1), 243–265.
- Kolditz, O., Bauer, S., Bilke, L., Böttcher, N., Delfs, J.-O., Fischer, T., ... others (2012). Opengeosys: an open-source initiative for numerical simulation of thermo-hydro-mechanical/chemical (thm/c) processes in porous media. *Environmental Earth Sciences*, 67(2), 589–599.
- Lade, P. V. (2001). Engineering properties of soils and typical correlations. In *Geotechnical and geoenvironmental engineering handbook* (pp. 43–67). Springer.
- Lambe, T. W., & Whitman, R. V. (1991). *Soil mechanics* (Vol. 10). John Wiley & Sons.
- McMillan, T. C., Rau, G. C., Timms, W. A., & Andersen, M. S. (2019, 6). Utilizing the Impact of Earth and Atmospheric Tides on Groundwater Systems: A Review Reveals the Future Potential. *Reviews of Geophysics*, 57(2), 281–315. Retrieved from <https://onlinelibrary.wiley.com/doi/abs/10.1029/2018RG000630> doi: 10.1029/2018RG000630
- Meinzer, O. E. (1939). *Ground water in the United States, a summary of ground-water conditions and resources, utilization of water from wells and springs, methods of scientific investigation, and literature relating to the subject* (-ed.; Tech. Rep.). U.S. G.P.O. Retrieved from <http://pubs.er.usgs.gov/publication/wsp836D>
- Merritt, M. L. (2004). *Estimating hydraulic properties of the {Floridan} aquifer system by analysis of earth-tide, ocean-tide, and barometric effects, {Collier and Hendry Counties, Florida}* (Tech. Rep. No. 034267). US Geol Surv.
- Pendiuk, J. E., Guarracino, L., Reich, M., Brunini, C., & Güntner, A. (2020). Estimating the specific yield of the pampeano aquifer, argentina, using superconducting gravimeter data. *Hydrogeology Journal*, 28(7), 2303–2313.
- Permann, C. J., Gaston, D. R., Andrš, D., Carlsen, R. W., Kong, F., Lindsay, A. D.,

- ... others (2020). Moose: Enabling massively parallel multiphysics simulation. *SoftwareX*, 11, 100430.
- Qu, J., & Cherkaoui, M. (2006). *Fundamentals of micromechanics of solids* (Vol. 735). Wiley Online Library.
- Rau, G. C. (2018). *PyGTide: A Python module and wrapper for ETERNA PREDICT to compute synthetic model tides on Earth*. Zenodo. Retrieved from <https://doi.org/10.5281/zenodo.1346260> doi: 10.5281/zenodo.1346260
- Rau, G. C., Cuthbert, M. O., Acworth, R. I., & Blum, P. (2020). Disentangling the groundwater response to earth and atmospheric tides to improve subsurface characterisation. *Hydrology and earth system sciences*, 24(12), 6033–6046.
- Rau, G. C., Cuthbert, M. O., Post, V. E., Schweizer, D., Acworth, R. I., Andersen, M. S., ... Ge, S. (2020). Future-proofing hydrogeology by revising groundwater monitoring practice. *Hydrogeology Journal*, 28(8), 2963–2969.
- Roeloffs, E. A., Burford, S. S., Riley, F. S., & Records, A. W. (1989). Hydrologic effects on water level changes associated with episodic fault creep near Parkfield, California. *Journal of Geophysical Research*, 94(B9), 12387. Retrieved from <http://doi.wiley.com/10.1029/JB094iB09p12387> doi: 10.1029/jb094ib09p12387
- Rojstaczer, S. (1988). Determination of fluid flow properties from the response of water levels in wells to atmospheric loading. *Water Resources Research*, 24(11), 1927–1938.
- Rojstaczer, S., & Agnew, D. C. (1989). The influence of formation material properties on the response of water levels in wells to earth tides and atmospheric loading. *Journal of Geophysical Research: Solid Earth*, 94(B9), 12403–12411.
- Rojstaczer, S., & Riley, F. S. (1990). Response of the water level in a well to earth tides and atmospheric loading under unconfined conditions. *Water Resources Research*, 26(8), 1803–1817.
- Schweizer, D., Ried, V., Rau, G. C., Tuck, J. E., & Stoica, P. (2021, 2). Comparing Methods and Defining Practical Requirements for Extracting Harmonic Tidal Components from Groundwater Level Measurements. *Mathematical Geosciences*. Retrieved from <http://link.springer.com/10.1007/s11004-020-09915-9> doi: 10.1007/s11004-020-09915-9
- Settari, A., & Walters, D. A. (2001). Advances in coupled geomechanical and reservoir modeling with applications to reservoir compaction. *Spe Journal*, 6(03), 334–342.
- Sun, X., Shi, Z., & Xiang, Y. (2020). Frequency dependence of in situ transmissivity estimation of well-aquifer systems from periodic loadings. *Water Resources Research*, 56(11), e2020WR027536.
- Turnadge, C., Crosbie, R. S., Barron, O., & Rau, G. C. (2019). Comparing methods of barometric efficiency characterization for specific storage estimation. *Groundwater*, 57(6), 844–859.
- Van Camp, M., & Vauterin, P. (2005, 6). Tsoft: graphical and interactive software for the analysis of time series and Earth tides. *Computers & Geosciences*, 31(5), 631–640. Retrieved from <http://linkinghub.elsevier.com/retrieve/pii/S0098300404002456> doi: 10.1016/j.cageo.2004.11.015
- Verruijt, A. (2013). Theory and problems of poroelasticity. *Delft University of Technology*, 71.
- Verruijt, A., & Van Baars, S. (2007). *Soil mechanics*. VSSD Delft, the Netherlands.
- Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D., ... others (2020). Scipy 1.0: fundamental algorithms for scientific computing in python. *Nature methods*, 17(3), 261–272.
- Wang. (2017). *Theory of linear poroelasticity with applications to geomechanics and hydrogeology*. Princeton University Press.
- Wang, Doan, M.-L., Xue, L., & Barbour, A. J. (2018). Tidal response of groundwater in a leaky aquifer—application to oklahoma. *Water Resources Research*,

- 54(10), 8019–8033.
- Wang, & Manga, M. (2021). Response to tides, barometric pressure and seismic waves. *Water and Earthquakes*, 83–153.
- Wang, Zhu, A.-Y., Liao, X., Manga, M., & Wang, L.-P. (2019). Capillary effects on groundwater response to earth tides. *Water Resources Research*, 55(8), 6886–6895.
- Wang, C., & Zeng, Z. (2011). Overview of geomechanical properties of bakken formation in williston basin, north dakota. In *45th us rock mechanics/geomechanics symposium*.
- Wang, H. F. (2000). *Theory of Linear Poroelasticity with Applications to Geomechanics and Hydrogeology*. Princeton University Press. Retrieved from <https://press.princeton.edu/titles/7006.html>
- Wenzel, H.-G. (1996). The nanoGal software: Earth tide data processing package: Eterna 3.3. *Bulletin d'Informations des Marées Terrestres*, 124, 9425–9439.
- Wilkins, A., Green, C. P., & Ennis-King, J. (2020). Porousflow: a multiphysics simulation code for coupled problems in porous media. *Journal of Open Source Software*, 5(55), 2176.
- Wilkins, A., Green, C. P., & Ennis-King, J. (2021). An open-source multiphysics simulation code for coupled problems in porous media. *Computers & Geosciences*, 154, 104820.
- Xue, L., Brodsky, E. E., Erskine, J., Fulton, P. M., & Carter, R. (2016). A permeability and compliance contrast measured hydrogeologically on the san andreas fault. *Geochemistry, Geophysics, Geosystems*, 17(3), 858–871.
- Zhang, M., Hao, Y., Zhao, Z., Wang, T., & Yang, L. (2021). Estimation of coastal aquifer properties: A review of the tidal method based on theoretical solutions. *Wiley Interdisciplinary Reviews: Water*, 8(1), e1498.
- Zhu, A.-Y., & Wang. (2020). Response of leaky aquifers to earth tides—interpreted with numerical simulation. *Journal of Hydrology*, 581, 124458.